

## **TOWN OF WILTON** 22 TRAVER ROAD GANSEVOORT, NEW YORK 12831-9127

FAX (518) 587-2837 Website: www.townofwilton.com

(518) 587-1939, Ext. 603

E-mail: mmykins@townofwilton.com

Mark Mykins Senior Building Inspector Code Enforcement Officer Zoning Officer

John Herlihy Building Inspector & Code Enforcement Officer

### Marcus Hart

Asst. Building Inspector & Asst. Code Enforcement Officer

# **SOLID FUEL BURNING DEVICES & CHIMNEY PERMIT APPLICATION**

DATE:	PERMIT Number:
PROPERTY LOCATION:	
NAME:	
ADDRESS:	
PHONE NUMBER:	
TAX MAP NUMBER:	
CHIMNEY(S)	
MASONRY	METAL PIPING
Flue Size: Thimble Size: Footing Size:	Wall: single double triple Clean-out Door: Yes No Height Above Roof Line:
FACTORY BUILT FIREPLACE, FIREPL	ACE INSERT, WOODSTOVE
Make & Model:	
Make & Model: Insert:	
installer: Applicant:	Professional Contractor: Other
Wall Construction Nearest Stove:	Pipe: Stove:
Clearance to Nearest Combustible: Stove	Pipe: Stove:
Chimney:Standard Masonry: _ Date Chimney Last Cleaned and Inspecte	U.L. Material: For Existing Fireplace d:
Location in Dwelling:	

# NOTE: A COPY OF THE MANUFACTURERS INSTALLATION MANUAL <u>MUST</u> BE SUBMITTED WITH APPLICATION.

FIREPLACE		
Damper Size:	Flue Size:	
Ash Dump: Yes No	Fresh Air: Yes No	:

### **GENERAL REQUIREMENTS:**

- 1. Only **ONE** heating appliance per chimney.
- 2. All fireplaces must have fresh air and a clean out.
- 3. All single wall steel pipe must be at least 24 gauge.
- 4. Factory built chimney must be "listed" by national testing agency.
- 5. "Listed" chimney must be triple insulated as it passes through the structure.
- 6. Wall nearest stove pipe must be protected by a non-combustible material with 1" min. air space.
- 7. Non-combustible flooring for woodstoves must extend 18" beyond ash door and 6" beyond sides and back.
- 8. Fireplace hearth minimum depth 16" and must extend at least 8" beyond each side of the fireplace opening.
- 9. All "fuel chimneys" must maintain a 2" clearance from all combustibles.
- 10. Factory built chimneys if in a chase must have a fire stop every 8' maximum.
- 11. Masonry chimney clay flue must be 5/8" thick minimum.
- 12. Chimney must extend 3' above highest point that it passes through the roof, and min. 2' higher than any portion of the building within 10 feet.
- 13. All fireplaces must have glass doors.
- 14. Written certification by the installer certifying installation was done to NFPA 211, State and Local Codes.
- 15. ALL CHIMNEYS SHOULD BE CLEANED AND INSPECTED A MINIMUM OF ONCE A YEAR.

### **INSPECTIONS:**

- 1. Footing before pouring.
- 2. Chimney & Fireplace BEFORE adding insert.
- 3. Final inspection upon completion.

NOTE: MINIMUM 24 hours notice for all required inspections.

FEE:			÷
\$50.00 PER APPLICATION	ON.		
I have read the regular of Wilton.	tions above and agree to abi	de by these and all require	ments of the Town
Date:	Signature:		
	d) and permission granted (re		is hereby
· · · · · · · · · · · · · · · · · · ·	a, and permission grantes (re		
Date	Building Inspector		

,



### **TOWN OF WILTON** 22 TRAVER ROAD **GANSEVOORT, NEW YORK 12831-9127**

FAX (518) 587-2837 Website: www.townofwilton.com

(518) 587-1939, Ext. 603

E-mail: mmykins@townofwilton.com

Mark Mykins

Senior Building Inspector Code Enforcement Officer Zoning Officer

John Herlihy Building Inspector & Code Enforcement Officer

**Marcus Hart** 

Asst. Building Inspector

& Asst. Code Enforcement Officer

# SOLID/LIQUID FUEL BURNING DEVICE CERTIFICATION

To Whom It May Concern:					
The (woodstove(s)) (firepla	ce(s)) (circle one	) and ass	sociated chimne	ey, located at	
	and bu	ilt by			<del>-</del>
and installed on		confo	rm(s) to all bui	lding codes an	d
manufacturer's installation req	quirements as set	forth in	the Residential	Code of New	
York State and the National Fi	ire Protection Ag	gency as p	er Chapter 211	•	
· ·	A STORY		Signature of	Installation Co	ntractor
STATE OF NEW YORK COUNTY OF SARATOGA Sworn to this	_day of _, 2021.				
Notary Dublic					